

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL  
Revision date : 20.03.2023  
Print date : 17.10.2023

Version : 1.0.0

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

Master Mould RL  
Unique Formula Identifier : AV60-N0YY-U00V-REQW

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses

PC 35 - Washing and cleaning products

#### Sectors of use [SU]

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)  
Industrial uses

### 1.3 Details of the supplier of the safety data sheet

#### Supplier

Bio-Circle Surface Technology AG

**Street :** Aahusweg 16

**Postal code/City :** 6403 Küssnacht am Rigi

**Telephone :** 0041 41 878 1166

**Telefax :** 0041 41 878 1347

**Information contact :** service@bio-circle.ch

### 1.4 Emergency telephone number

+41 (0)442515151  
Schweizerisches Toxikologisches Informationszentrum, 145

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4 ; H302 - Acute toxicity (oral) : Category 4 ; Harmful if swallowed.  
Acute Tox. 4 ; H332 - Acute toxicity (inhalative) : Category 4 ; Harmful if inhaled.  
Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.  
Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

##### Hazard pictograms



Corrosion (GHS05) · Exclamation mark (GHS07)

##### Signal word

Danger

##### Hazard components for labelling

BENZYL ALCOHOL ; CAS No. : 100-51-6

FORMIC ACID 4 % ; CAS No. : 64-18-6

ISOTRIDECANOL, ETHOXYLATED ( >= 2.5 EO) ; CAS No. : 69011-36-5

AMIDES, C8-18 (EVEN NUMBERED) AND C18 (UNSATD.), N,N-BIS(HYDROXYETHYL) ; CAS No. : 68155-07-7

##### Hazard statements

H318 Causes serious eye damage.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL  
Revision date : 20.03.2023  
Print date : 17.10.2023

Version : 1.0.0

H302+H332 Harmful if swallowed or if inhaled.  
H315 Causes skin irritation.

#### Precautionary statements

P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P332+P313 If skin irritation occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor/.../ if you feel unwell.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P302+P352 IF ON SKIN: Wash with plenty of water/....

#### 2.3 Other hazards

None

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

BENZYL ALCOHOL ; REACH No. : 01-2119492630-38-XXXX ; EC No. : 202-859-9; CAS No. : 100-51-6

Weight fraction :  $\geq 50 - < 100$  %  
Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Acute Tox. 4 ; H332 Eye Irrit. 2 ; H319

FORMIC ACID ; REACH No. : 01-2119491174-37-XXXX ; EC No. : 200-579-1; CAS No. : 64-18-6

Weight fraction :  $\geq 2 - < 5$  %  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Met. Corr. 1 ; H290 Acute Tox. 3 ; H331 Skin Corr. 1A ; H314 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 EUH071  
Substance with a common (EC) occupational exposure limit value.

Specific Conc. Limits : Skin Corr. 1A ; H314: C  $\geq 90$  % • Eye Dam. 1 ; H318: C  $\geq 10$  % • Skin Corr. 1B ; H314: C  $\geq 10$  % • Skin Corr. 1C ; H314: C  $\geq 10$  % • Eye Irrit. 2 ; H319: C  $\geq 2$  % • Skin Irrit. 2 ; H315: C  $\geq 2$  %

ISOTRIDECANOL, ETHOXYLATED ( $\geq 2.5$  EO) ; REACH No. : (Polymer) ; EC No. : 931-138-8; CAS No. : 69011-36-5

Weight fraction :  $\geq 1 - < 5$  %  
Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Acute Tox. 4 ; H302  
Specific Conc. Limits : Eye Dam. 1 ; H318: C  $\geq 10$  %

AMIDES, C8-18 (EVEN NUMBERED) AND C18 (UNSATD.), N,N-BIS(HYDROXYETHYL) ; REACH No. : 01-2119490100-53-XXXX ; EC No. : 931-329-6; CAS No. : 68155-07-7

Weight fraction :  $\geq 1 - < 2,5$  %  
Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Skin Irrit. 2 ; H315 Aquatic Chronic 2 ; H411

#### Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

#### Following inhalation

Remove casualty to fresh air and keep warm and at rest.

#### In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Rub greasy ointment into the skin.

#### After eye contact

Protect uninjured eye. In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL  
Revision date : 20.03.2023  
Print date : 17.10.2023

Version : 1.0.0

holding eyelids apart and consult an ophthalmologist.

### Following ingestion

Rinse mouth thoroughly with water. Let 1 glass of water be drunken in little sips (dilution effect). Do NOT induce vomiting. Call a physician immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye irritation. Causes skin irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

None

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water Foam Extinguishing powder Carbon dioxide (CO<sub>2</sub>) Sand Nitrogen Extinguishing blanket

#### Unsuitable extinguishing media

Full water jet

### 5.2 Special hazards arising from the substance or mixture

#### Hazardous combustion products

In case of fire may be liberated: Carbon monoxide , Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

### 5.4 Additional information

The product itself does not burn. Co-ordinate fire-fighting measures to the fire surroundings.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Special danger of slipping by leaking/spilling product.

### 6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### 6.3 Methods and material for containment and cleaning up

Clear spills immediately. Wipe up with absorbent material (eg. cloth, fleece). Wash with plenty of water. Treat the recovered material as prescribed in the section on waste disposal.

### 6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Keep container tightly closed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep/Store only in original container. Protect against : Frost .

### 7.3 Specific end use(s)

Observe technical data sheet. Observe instructions for use.

## SECTION 8: Exposure controls/personal protection

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL  
Revision date : 20.03.2023  
Print date : 17.10.2023

Version : 1.0.0

## 8.1 Control parameters

### Occupational exposure limit values

BENZYL ALCOHOL ; CAS No. : 100-51-6

Limit value type (country of origin) : MAK ( ch )  
Limit value : 5 ppm / 22 mg/m<sup>3</sup>  
Remark : H; SSc  
Version : 09.03.2021

FORMIC ACID ; CAS No. : 64-18-6

Limit value type (country of origin) : KZGW ( CH )  
Limit value : 10 ppm / 19 mg/m<sup>3</sup>  
Remark : SSc  
Version :

Limit value type (country of origin) : MAK ( CH )  
Limit value : 5 ppm / 9,5 mg/m<sup>3</sup>  
Remark : SSc  
Version :

Limit value type (country of origin) : TWA ( EC )  
Limit value : 5 ppm / 9 mg/m<sup>3</sup>  
Version : 20.06.2019

### DNEL-/PNEC-values

#### DNEL/DMEL

BENZYL ALCOHOL ; CAS No. : 100-51-6

Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 90 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 450 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 9,5 mg/kg  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Short-term  
Limit value : 47 mg/kg

FORMIC ACID ; CAS No. : 64-18-6

Limit value type : DNEL worker (local)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 9,5 mg/m<sup>3</sup>  
Limit value type : DNEL worker (local)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 19 mg/m<sup>3</sup>

ISOTRIDECANOL, ETHOXYLATED ( >= 2.5 EO ) ; CAS No. : 69011-36-5

Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 294 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL  
Revision date : 20.03.2023  
Print date : 17.10.2023

Version : 1.0.0

Exposure frequency : Long-term  
Limit value : 2080 mg/kg  
AMIDES, C8-18 (EVEN NUMBERED) AND C18 (UNSATD.), N,N-BIS(HYDROXYETHYL) ; CAS No. : 68155-07-7  
Limit value type : DNEL Consumer (local)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : = 0,056 mg/cm<sup>2</sup>  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : = 2,5 mg/kg  
Assessment factor : 1 D  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : = 21,73 mg/m<sup>3</sup>  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Oral  
Exposure frequency : Long-term  
Limit value : = 6,25 mg/kg  
Assessment factor : 1 D  
Limit value type : DNEL worker (local)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : = 0,0936 mg/cm<sup>2</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : = 4,16 mg/kg  
Assessment factor : 1 D  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : = 73,4 mg/m<sup>3</sup>

## PNEC

AMIDES, C8-18 (EVEN NUMBERED) AND C18 (UNSATD.), N,N-BIS(HYDROXYETHYL) ; CAS No. : 68155-07-7  
Limit value type : PNEC (Aquatic, freshwater)  
Limit value : 0,007 mg/l  
Limit value type : PNEC (Aquatic, intermittent release)  
Limit value : 0,024 mg/l  
Limit value type : PNEC (Aquatic, marine water)  
Limit value : 0,0007 mg/l  
Limit value type : PNEC (Sediment, freshwater)  
Limit value : 0,195 mg/kg  
Limit value type : PNEC (Sediment, marine water)  
Limit value : 0,0195 mg/kg  
Limit value type : PNEC (Soil)  
Limit value : 0,0348 mg/kg  
Limit value type : PNEC (Sewage treatment plant)  
Limit value : 830 mg/l

## 8.2 Exposure controls

### Personal protection equipment

#### Eye/face protection

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL  
Revision date : 20.03.2023  
Print date : 17.10.2023

Version : 1.0.0



Wear suitable safety goggles in case of splash.

**Suitable eye protection**  
EN 166.

## Skin protection

**Hand protection**



**Suitable gloves type** : EN 374.  
**Suitable material** : NBR (Nitrile rubber)  
**Breakthrough time** : 480 min.  
**Thickness of the glove material** : 0.4 mm

**Remark** : The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

## Respiratory protection



Respiratory protection necessary at: exceeding exposure limit values

**Suitable respiratory protection apparatus**

Combination filtering device  
Type : A

**Remark**

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

## General information

Do not put any product-impregnated cleaning rags into your trouser pockets. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. P362+P364 - Take off contaminated clothing and wash it before reuse. P264 - Wash hands thoroughly after handling.

### 8.3 Additional information

No tests have been performed. Selection made for preparations according to the best available knowledge and information on ingredients. In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state** : Liquid

**Colour** : colourless

#### Odour

characteristic

#### Safety characteristics

**Melting point/freezing point** : ( 1013 hPa ) not determined

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL  
Revision date : 20.03.2023  
Print date : 17.10.2023

Version : 1.0.0

Initial boiling point and boiling range :	( 1013 hPa )	>	100 °C	
Flash point :		>	85 °C	DIN EN ISO 13736
Auto-ignition temperature :			none	
Flammability :			non-flammable	
Lower explosion limit :			not relevant	
Upper explosion limit :			not relevant	
Vapour pressure :	( 50 °C )		not relevant	
Density :	( 20 °C )		1,04 - 1,053 g/cm <sup>3</sup>	
Solvent separation test :	( 20 °C )		not relevant	
Water solubility :	( 20 °C )		partially soluble	
pH :	( 20 °C / 100 g/l )		3	
Cinematic viscosity :	( 20 °C )	<	30 mm <sup>2</sup> /s	
Relative vapour density :	( 20 °C )		not determined	
Maximum VOC content (EC) :			4,5 Weight-%	
Maximum VOC content (Switzerland) :			93,6 Weight-%	
Taxable VOC content (Switzerland) :			89,1 Weight-%	

## 9.2 Other information

No further relevant information available.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material is considered to be non-reactive under normal use conditions.

### 10.2 Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

No information available.

### 10.5 Incompatible materials

No information available.

### 10.6 Hazardous decomposition products

No known hazardous decomposition products.  
Decomposition products in case of fire: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Harmful by inhalation and if swallowed.

#### Acute oral toxicity

Parameter :	ATEmix
Exposure route :	Oral
Effective dose :	> 500 mg/m <sup>3</sup>
Parameter :	LD50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )
Exposure route :	Oral
Species :	Rat
Effective dose :	1230 - 1620 mg/kg
Parameter :	LD50 ( FORMIC ACID ; CAS No. : 64-18-6 )
Exposure route :	Oral
Species :	Rat
Effective dose :	730 mg/kg

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL  
Revision date : 20.03.2023  
Print date : 17.10.2023

Version : 1.0.0

Method : OECD 401  
Parameter : LD50 ( Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl) ; CAS No. : 8051-30-7 )  
Exposure route : Oral  
Species : Rat  
Effective dose : > 5000 mg/kg  
Parameter : LD50 ( ISOTRIDEKANOL, ETHOXYLATED ( >= 2.5 EO ) ; CAS No. : 9043-30-5 )  
Exposure route : Oral  
Species : Rat  
Effective dose : 300 - 2000 mg/kg  
Method : OECD 423

### Acute dermal toxicity

Parameter : ATEmix  
Exposure route : Dermal  
Effective dose : > 2000 mg/kg  
Parameter : LD50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : 2000 mg/kg  
Parameter : LD50 ( FORMIC ACID ; CAS No. : 64-18-6 )  
Exposure route : Dermal  
Species : Rat  
Effective dose : > 2000 mg/kg  
Method : OECD 402  
Parameter : LD50 ( Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl) ; CAS No. : 8051-30-7 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : > 2000 mg/kg  
Parameter : LD50 ( ISOTRIDEKANOL, ETHOXYLATED ( >= 2.5 EO ) ; CAS No. : 9043-30-5 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : > 2000 mg/kg  
Method : OECD 402

### Acute inhalation toxicity

Parameter : ATEmix  
Exposure route : Inhalation (vapour)  
Effective dose : > 10 mg/m<sup>3</sup>  
Parameter : LC50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : > 4178 mg/m<sup>3</sup>  
Exposure time : 4 h  
Method : OECD 403  
Parameter : LC50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 1000 ppm  
Exposure time : 8 h  
Parameter : LC50 ( FORMIC ACID ; CAS No. : 64-18-6 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 7,4 mg/l  
Exposure time : 4 h  
Method : OECD 403

### Corrosion



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL  
Revision date : 20.03.2023  
Print date : 17.10.2023

Version : 1.0.0

## Skin corrosion/irritation

Causes skin irritation.

## Serious eye damage/eye irritation

Causes serious eye damage.

## Respiratory or skin sensitisation

### Skin sensitisation

Parameter : Skin sensitisation ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )

No further relevant information available.

### Sensitisation to the respiratory tract

No further relevant information available.

## CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

### Carcinogenicity

No further relevant information available.

### Germ cell mutagenicity

No further relevant information available.

### Reproductive toxicity

No further relevant information available.

## STOT-single exposure

No further relevant information available.

## STOT-repeated exposure

No further relevant information available.

## Aspiration hazard

No further relevant information available.

## 11.2 Information on other hazards

### Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

### Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

### Other adverse effects

Has degreasing effect on the skin.

### Additional information

Preparation not tested. The statement is derived from the properties of the single components.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity

##### Acute (short-term) fish toxicity

Parameter :	LC50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )
Species :	Pimephales promelas (fathead minnow)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	460 mg/l
Exposure time :	96 h
Parameter :	LC50 ( FORMIC ACID ; CAS No. : 64-18-6 )
Species :	Danio rerio (zebrafish)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	130 mg/l
Exposure time :	96 h
Method :	OECD 203
Parameter :	LC50 ( Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl) ;

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL  
Revision date : 20.03.2023  
Print date : 17.10.2023

Version : 1.0.0

CAS No. : 8051-30-7 )  
Species : Fish  
Evaluation parameter : Acute (short-term) fish toxicity  
Effective dose : 2,4 mg/l  
Exposure time : 96 h  
Parameter : LC50 ( ISOTRIDECANOL, ETHOXYLATED ( >= 2.5 EO ) ; CAS No. : 9043-30-5 )  
Species : Cyprinus carpio (Common Carp)  
Evaluation parameter : Acute (short-term) fish toxicity  
Effective dose : > 1 mg/l  
Exposure time : 96 h  
Method : OECD 203

### Chronic (long-term) fish toxicity

Parameter : NOEC ( Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl) ; CAS No. : 8051-30-7 )  
Species : Fish  
Evaluation parameter : Chronic (long-term) fish toxicity  
Effective dose : 0,32 mg/l  
Exposure time : 28 D  
Method : OECD 204

### Acute (short-term) toxicity to crustacea

Parameter : EC50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Acute (short-term) toxicity to crustacea  
Effective dose : 230 mg/ml  
Exposure time : 48 h  
Method : OECD 202

Parameter : EC50 ( FORMIC ACID ; CAS No. : 64-18-6 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Acute (short-term) toxicity to crustacea  
Effective dose : 365 mg/l  
Exposure time : 48 h  
Method : OECD 202

Parameter : NOEC ( FORMIC ACID ; CAS No. : 64-18-6 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Acute (short-term) toxicity to crustacea  
Effective dose : 180 mg/l  
Exposure time : 48 h  
Method : OECD 202

Parameter : EC50 ( Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl) ; CAS No. : 8051-30-7 )  
Species : Daphnia  
Evaluation parameter : Acute (short-term) toxicity to crustacea  
Effective dose : 3,2 mg/l  
Exposure time : 48 h  
Method : OECD 202

Parameter : EC50 ( ISOTRIDECANOL, ETHOXYLATED ( >= 2.5 EO ) ; CAS No. : 9043-30-5 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Acute (short-term) toxicity to crustacea  
Effective dose : > 1 mg/l  
Exposure time : 48 h  
Method : OECD 202

### Acute (short-term) toxicity to algae and cyanobacteria

Parameter : EC50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Species : Pseudokirchneriella subcapitata  
Evaluation parameter : Inhibition of growth rate  
Effective dose : 770 mg/l

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL  
Revision date : 20.03.2023  
Print date : 17.10.2023

Version : 1.0.0

Exposure time : 72 h  
Method : OECD 201  
Parameter : EC50 ( FORMIC ACID ; CAS No. : 64-18-6 )  
Species : Pseudokirchneriella subcapitata  
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria  
Effective dose : 1240 mg/l  
Exposure time : 72 h  
Method : OECD 201  
Parameter : ErC50 ( Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl) ; CAS No. : 8051-30-7 )  
Species : Algae  
Evaluation parameter : Inhibition of growth rate  
Effective dose : 18,6 mg/l  
Exposure time : 72 h  
Method : Regulation (EC) No. 440/2008, Annex C.3  
Parameter : EC50 ( ISOTRIDEKANOL, ETHOXYLATED ( >= 2.5 EO ) ; CAS No. : 9043-30-5 )  
Species : Desmodesmus subspicatus  
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria  
Effective dose : > 1 mg/l  
Exposure time : 72 h  
Method : OECD 201

#### Chronic (long-term) toxicity to aquatic algae and cyanobacteria

Parameter : NOEC ( Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl) ; CAS No. : 8051-30-7 )  
Species : Algae  
Evaluation parameter : Chronic (long-term) toxicity to aquatic algae and cyanobacteria  
Effective dose : 2 mg/l  
Exposure time : 72 h

#### Toxicity to microorganisms

Parameter : EC50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Species : Toxicity to microorganisms  
Effective dose : 2100 mg/l  
Exposure time : 49 h  
Parameter : EC50 ( FORMIC ACID ; CAS No. : 64-18-6 )  
Species : Pseudomonas putida  
Effective dose : 46,7 mg/l  
Exposure time : 17 h  
Parameter : EC50 ( ISOTRIDEKANOL, ETHOXYLATED ( >= 2.5 EO ) ; CAS No. : 9043-30-5 )  
Species : Toxicity to microorganisms  
Effective dose : > 140 mg/l

## 12.2 Persistence and degradability

### Biodegradation

Parameter : Biodegradation ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Inoculum : Biodegradation  
Degradation rate : 95 - 97 %  
Test duration : 21 D  
Evaluation : Readily biodegradable (according to OECD criteria).  
Method : OECD 301A  
Parameter : DOC reduction ( FORMIC ACID ; CAS No. : 64-18-6 )  
Inoculum : Biodegradation  
Evaluation parameter : Aerobic  
Degradation rate : 92 %  
Test duration : 28 D  
Method : OECD 301D  
Parameter : Biodegradation ( Amides, C8-18 (even numbered) and C18-unsatd., N,N-bis(hydroxyethyl) ; CAS No. : 8051-30-7 )

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL  
Revision date : 20.03.2023  
Print date : 17.10.2023

Version : 1.0.0

Inoculum :	Degree of elimination
Degradation rate :	92,5 %
Test duration :	28 D
Evaluation :	Readily biodegradable (according to OECD criteria).
Method :	OECD 301B
Parameter :	Biodegradation ( ISOTRIDEKANOL, ETHOXYLATED ( $\geq$ 2.5 EO) ; CAS No. : 9043-30-5 )
Inoculum :	Degree of elimination
Evaluation parameter :	Anaerobic
Degradation rate :	> 60 %
Test duration :	60 D
Parameter :	CO2 formation (% of the theoretical value) ( ISOTRIDEKANOL, ETHOXYLATED ( $\geq$ 2.5 EO) ; CAS No. : 9043-30-5 )
Inoculum :	Degree of elimination
Evaluation parameter :	Aerobic
Degradation rate :	> 60 %
Test duration :	28 D
Evaluation :	Readily biodegradable (according to OECD criteria).
Method :	OECD 301B

### 12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

### 12.4 Mobility in soil

No information available.

### 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7 Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Ordinance on the avoidance and disposal of waste (ADWO) SR 814.600.

##### Before intended use

##### Waste code according to the lists for the movement of waste

07 06 01\* (Aqueous washing liquids and mother liquors)

20 01 29\* (Detergents containing hazardous substances)

##### Other disposal recommendations

Dispose of waste according to applicable legislation. Dispose of contents/container to an appropriate recycling or disposal facility. Contaminated packages must be completely emptied and can be re-used following proper cleaning.

Handle contaminated packages in the same way as the substance itself.

### 13.2 Additional information

The allocation of waste identity numbers/waste descriptions must be carried out according to the VVEA, specific to the industry and process.

## SECTION 14: Transport information

### 14.1 UN number

No dangerous good in sense of these transport regulations.

### 14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL  
Revision date : 20.03.2023  
Print date : 17.10.2023

Version : 1.0.0

## 14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

## 14.4 Packing group

No dangerous good in sense of these transport regulations.

## 14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

## 14.6 Special precautions for user

None

## 14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

##### Authorisations and/or restrictions on use

##### Restrictions on use

Use restriction according to REACH annex XVII, no. : 3, 40, 75

##### Other regulations (EU)

##### Labelling for contents according to regulation (EC) No. 648/2004

< 5 % amphoteric surfactants

< 5 % non-ionic surfactants

Contains the following substances: BENZYL ALCOHOL

##### National regulations

##### Restrictions of occupation

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

##### Other regulations, restrictions and prohibition regulations

##### Switzerland

Chemicals Ordinance, ChemO (SR 813.11)

Chemical Risk Reduction Ordinance, ORRChem (SR 814.81)

### 15.2 Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

## SECTION 16: Other information

### 16.1 Indication of changes

None

### 16.2 Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (Europäisches Übereinkommen über die Beförderung gefährlicher Güter auf der Straße)

AOX: adsorbierbare organisch gebundene Halogene

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

CAS: Chemical Abstracts Service (Unterabteilung der American Chemical Society)

CLP: Verordnung (EG) Nr. 1272/2008 über die Einstufung, Kennzeichnung und Verpackung von Stoffen und Gemischen (Classification Labelling and Packaging)

EAK / AVV: europäischer Abfallartenkatalog / Abfallverzeichnis-Verordnung

ECHA: Europäische Chemikalienagentur (European Chemicals Agency)

EINECS: : Altstoffverzeichnis (European Inventory of Existing Commercial Chemical Substances)

GHS: Global harmonisiertes System zur Einstufung und Kennzeichnung von Chemikalien (Globally Harmonized System of Classification and Labelling of Chemicals)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Master Mould RL  
Revision date : 20.03.2023  
Print date : 17.10.2023

Version : 1.0.0

IATA: Internationale Luftverkehrs-Vereinigung (International Air Transport Association)  
ICAO: Internationale Zivilluftfahrtorganisation (International Civil Aviation Organization)  
IMDG: Gefahrgutkennzeichnung für gefährliche Güter im Seeschiffverkehr (International Maritime Code for Dangerous Goods)  
RID: Regelung zur internationalen Beförderung gefährlicher Güter im Schienenverkehr (Règlement concernant le transport international ferroviaire de marchandises dangereuses)  
TRGS: Technische Regel für den Umgang mit Gefahrstoffen  
VbF: Verordnung über brennbare Flüssigkeiten  
VOC: flüchtige organische Verbindung (volatile organic compound)  
VVEA: Verordnung über die Vermeidung und die Entsorgung von Abfällen  
VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe  
WGK: Wassergefährdungsklasse

### 16.3 Key literature references and sources for data

DGUV: GESTIS-Stoffdatenbank  
ECHA: Classification And Labelling Inventory  
ECHA: Pre-registered Substances  
ECHA: Registered Substances  
EC\_Safety Data Sheet of Suppliers  
ESIS: European Chemical Substances Information System  
GDL: Gefahrstoffdatenbank der Länder  
UBA Rigoletto: Wassergefährdende Stoffe  
Regulation (EC) No. 1907/2006 of the European Parliament and of the Council  
|-> COMMISSION REGULATION (EU) 2020/878 of 18 June 2020  
Regulation (EC) No. 1272/2008 of the European Parliament and of the Council

### 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].  
Evaluation :  
Acute Toxicity (oral), Category 4 : Calculation method.  
Acute Toxicity (inhalation), Category 4 : Calculation method.  
Skin Irrit. 2 : Calculation method.  
Eye Dam. 1 : Calculation method.

### 16.5 Relevant H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

### 16.6 Training advice

None

### 16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.